

Vegetation Control Systems

Manufactured by U-TECK

P.O. Box 2484, Fayetteville, North Carolina 28302
(800) 542-7011 • Fax: (910) 483-0784

WeedEnder.com



Features

- Controls unwanted vegetation
- Reduces runoff
- No herbicides or poisons
- Easy to install
- Environmentally safe
- Conforms to any shape
- Designed to be abused
- Cost-effective
- Maintenance-free
- Helps control erosion
- Long-lasting
- No disposal problems
- Reusable

This product is designed to control the growth of unwanted vegetation in an environmentally safe manner. This is accomplished without adding to your runoff problems, as would be the case when using asphalt, concrete, or other nonporous weed-control methods.

This type of roll is standard for use on new construction or where guardrail is not attached to the guardrail post. The roll is punched with a hole larger than the actual size of your guardrail post. The standard spacing for this punch-out is 6'3" center of hole to center of hole. Some guardrails require spacing of 12'6". We can accommodate any consistent spacing. The punch-out is also centered in the width unless otherwise specified.

WeedEnder® Punched Rolls have punch-outs and are available in different lengths and widths. The standard length is usually 250' long. This may vary because of the millrun when the material is originally made. Each roll will be clearly marked with the footage on each roll. (Your order will total the correct length.) You may also order odd-size lengths to fit specific needs. This is usually the case on every estimate. Widths may be any width from 1' to 6'. The standard for single guardrail is 3' to 4'. The standard for double guardrail is 4' to 6'. WeedEnder® rolls may be joined together for wider widths.

WeedEnder Installations

